



- ▶ WEBAC® 5620 is a low viscosity liquid bituminous emulsion. It is designed as a primer for dry or slightly damp mineral substrates.

Range of application

- Primer for bituminous thick coatings

Property

- Bituminous primer
- Ready to use

Technical data

	Values
Density, 20 °C / 68 °F (EN 52 004)	≈ 1.0 kg/l
Solids content	> 30%

The specified data are values determined under laboratory conditions and are subject to a certain fluctuation. Deviations are possible in practice depending on the respective object situation.

Product data

Application	By brush or wide brush
Material consumption	≈ 0.1–0.3 kg/m ²
Packing	Unit 10 l
Storage	<ul style="list-style-type: none"> • Between 5 °C / 41 °F and 30 °C / 86 °F • Protect from frost • Protect from moisture, heat and light • In original, sealed containers

WEBAC-Chemie GmbH
Fahrenberg 22
22885 Barsbüttel
Germany
Tel. +49 40 67057-0
Fax +49 40 6703227
info@webac.de

www.webac.de

Surface Sealings

WEBAC® 5620



Preparatory work

Structural analysis:

- Nature of the substrate
- Structural conditions (temperature and air moisture)
- Water load classes
- Existing surface interruptions due to fitted structures (e.g. pipe ducts)

This provides following information:

- Pretreatment of the substrate
- Substrates must be free of loose and separative substances
- Pretreat substrate to obtain a closed, smooth surface of good grip
- Existing, well-adhering bituminous coatings can be reworked after cleaning



Mixing

- Material is ready to use, stir material thoroughly



Application instruction

- Protect from dirt
- Only use pure WEBAC material without any residues of cleaning agents or other impurity



Application

- Apply to substrate by smoothing trowel or trowel
- Air moisture and light influence the curing speed



Cleaning

- Clean the equipment with water
- Remove cured residues with white spirit



Occupational safety

The safety regulations of the industrial trade associations and the WEBAC Safety Data Sheets are to be observed at all times when working with this product. Safety data sheets according to Regulation (EC) No. 1907/2006 (REACH) must be accessible to all persons responsible for occupational safety, health protection and the handling of materials. For further information, please see the separate information sheet "Occupational Safety" in our product catalog or www.webac-grouts.com.



Waste disposal

In Germany, empty containers can be disposed of via "Interseroh Dienstleistungs GmbH" observing the respective terms and conditions. It is not possible to dispose of containers at production facilities or delivery warehouses. For more detailed information, please see the separate information sheet "Information on the disposal and return of WEBAC packaging" in our product catalog or www.webac-grouts.com and the safety data sheets.

WEBAC-Chemie GmbH
Fahrenberg 22
22885 Barsbüttel
Germany
Tel. +49 40 67057-0
Fax +49 40 6703227
info@webac.de

www.webac.de