

Special Construction Products



WEBAC® Back Rod for Joint Filling

► WEBAC® Back Rods for Joint Filling are used for spacing and designing expansion joints.

Range of application


- Limitation of joint depth
- Back filling of joints

Properties

- Closed cell structure – not water absorbent
- High elasticity and adaptability
- Made of polyethylene – prevents three-point-adhesion

Example

Meaning of the icons ► WEBAC Product Catalog, www.webac.de or www.webac-grouts.com



WEBAC-Chemie GmbH
Fahrenberg 22
22885 Barsbüttel
Germany
Tel. +49 40 67057-0
Fax +49 40 6703227
info@webac.de

www.webac.de

Technical data

	Values
Form	Round profile Ø 6, 8, 10, 15 mm
Apparent density	≈ 23 kg/m ³
Temperature resistance	up to ≈ 60 °C / 140 °F

The specified data are values determined under laboratory conditions and are subject to a certain fluctuation. Deviations are possible in practice depending on the respective object situation.

► Technical Information

All the data indicated in this technical data sheet and any related information provided by our employees are of an advisory nature representing our current state of knowledge and in no way binding. As the exact chemical, technical and physical conditions of the actual application are beyond WEBAC's control, this information does not preclude examination of the products and/or procedures for the intended application and surface by the user. WEBAC is thus unable to guarantee results. The user is fully responsible for the observation of existing regulations and conditions when using the products.
© WEBAC-Chemie GmbH. Version 03/17

Special Construction Products

WEBAC® Back Rod for Joint Filling

Product data

Installation	<ul style="list-style-type: none"> • Manually • Make sure that the back rod for joint filling is compressed by approx. 25% • Do not push into the joint using a sharp object 											
Packing	<table border="1"> <thead> <tr> <th>Dimension</th> <th>Unit</th> </tr> </thead> <tbody> <tr> <td>Ø 6 mm</td> <td>100 m</td> </tr> <tr> <td>Ø 8 mm</td> <td>100 m</td> </tr> <tr> <td>Ø 10 mm</td> <td>100 m</td> </tr> <tr> <td>Ø 15 mm</td> <td>100 m</td> </tr> </tbody> </table>	Dimension	Unit	Ø 6 mm	100 m	Ø 8 mm	100 m	Ø 10 mm	100 m	Ø 15 mm	100 m	
Dimension	Unit											
Ø 6 mm	100 m											
Ø 8 mm	100 m											
Ø 10 mm	100 m											
Ø 15 mm	100 m											
Storage	Dry and protect from mechanical damage											

WEBAC-Chemie GmbH
Fahrenberg 22
22885 Barsbüttel
Germany
Tel. +49 40 67057-0
Fax +49 40 6703227
info@webac.de

www.webac.de

Occupational safety

The safety regulations of the industrial trade associations and the WEBAC Safety Data Sheets are to be observed at all times when working with this product. Safety data sheets according to Regulation (EC) No. 1907/2006 (REACH) must be accessible to all persons responsible for occupational safety, health protection and the handling of materials. For further information, please see the separate information sheet "Occupational Safety" in our product catalog or www.webac-grouts.com.

Waste disposal

In Germany, empty containers can be disposed of via "Interseroh Dienstleistungs GmbH" observing the respective terms and conditions. It is not possible to dispose of containers at production facilities or delivery warehouses. For more detailed information, please see the separate information sheet "Information on the disposal and return of WEBAC packaging" in our product catalog or www.webac-grouts.com and the safety data sheets.

► Technical Information

All the data indicated in this technical data sheet and any related information provided by our employees are of an advisory nature representing our current state of knowledge and in no way binding. As the exact chemical, technical and physical conditions of the actual application are beyond WEBAC's control, this information does not preclude examination of the products and/or procedures for the intended application and surface by the user. WEBAC is thus unable to guarantee results. The user is fully responsible for the observation of existing regulations and conditions when using the products.
© WEBAC-Chemie GmbH. Version 03/17