

Cleaner

WEBAC® Cleaner

- ▶ WEBAC Cleaners are designed for cleaning pumps and equipment as well as for dissolving cured resins.

Range of application

WEBAC® Cleaner A

- Cleaning and rinsing of injection pumps and equipment
- Removal of liquid epoxy and PU resins

WEBAC® Cleaner B

- Dissolving of cured resins

WEBAC® Lubricant

- Care product for pumps

WEBAC-Chemie GmbH
Fahrenberg 22
22885 Barsbüttel
Germany
Tel. +49 40 67057-0
Fax +49 40 6703227
info@webac.de

www.webac.de

Properties

- CFC-, FC- and chlorine-free
- Odorless
- No explosion protection required

Application instruction

WEBAC® Cleaner B

- Crystallization is possible below 10 °C / 50 °F
- This process is reversible by storage above 10 °C / 50 °F

▶ Technical Information

All the data indicated in this technical data sheet and any related information provided by our employees are of an advisory nature representing our current state of knowledge and in no way binding. As the exact chemical, technical and physical conditions of the actual application are beyond WEBAC's control, this information does not preclude examination of the products and/or procedures for the intended application and surface by the user. WEBAC is thus unable to guarantee results. The user is fully responsible for the observation of existing regulations and conditions when using the products.
© WEBAC-Chemie GmbH. Version 03/17

Cleaner

WEBAC® Cleaner

Product data

	WEBAC® Cleaner A	WEBAC® Cleaner B	WEBAC® Lubricant
Packing	Unit 11 kg	Unit 10.5 kg	Unit 10 kg 5 kg
Storage	<ul style="list-style-type: none"> • WEBAC® Cleaner A and WEBAC® Lubricant are frost resistant • WEBAC® Cleaner B: 10 °C / 50 °F – 30 °C / 86 °F • Protect from moisture and light • In original, sealed containers 		

WEBAC-Chemie GmbH
 Fahrenberg 22
 22885 Barsbüttel
 Germany
 Tel. +49 40 67057-0
 Fax +49 40 6703227
 info@webac.de

www.webac.de

Occupational safety

The safety regulations of the industrial trade associations and the WEBAC Safety Data Sheets are to be observed at all times when working with this product. Safety data sheets according to Regulation (EC) No. 1907/2006 (REACH) must be accessible to all persons responsible for occupational safety, health protection and the handling of materials. For further information, please see the separate information sheet "Occupational Safety" in our product catalog or www.webac-grouts.com.

Waste disposal

In Germany, empty containers can be disposed of via "Interseroh Dienstleistungs GmbH" observing the respective terms and conditions. It is not possible to dispose of containers at production facilities or delivery warehouses. For more detailed information, please see the separate information sheet "Information on the disposal and return of WEBAC packaging" in our product catalog or www.webac-grouts.com and the safety data sheets.